



## China abec 7 Bearing Supplier



Used For Motorcycle NSK 6204 6204/P6  
6204/P53Z2 Motorcycle Bearing

Bearing No. 6204

6204 Bearing 2D drawings and 3D CAD models

Size	20x47x14 mm
Bore Diameter	20 mm
Outer Diameter	47 mm
Width	14 mm
d	20 mm
D	47 mm
B	14 mm
C	14 mm
r min.	1 mm
da min.	25 mm
da max	26,5 mm
Da max.	42 mm
ra max.	1 mm
Weight	0,107 Kg
Basic dynamic load rating (C)	12,8 kN
Basic static load rating (C0)	6,6 kN
(Grease) Lubrication Speed	15 000 r/min
(Oil) Lubrication Speed	18 000 r/min
Category	Single Row Ball Bearings
Inventory	6.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.1
EAN	0029176014215
Product Group	B00308



## China abec 7 Bearing Supplier

Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Item Number	6204
Weight / LBS	0.23
Bore	0.787 Inch   20 Millimeter
Outside Diameter	1.85 Inch   47 Millimeter
Outer Race Width	0.551 Inch   14 Millimeter
bore diameter:	20 mm
closure type:	Open
outside diameter:	47 mm
internal clearance:	Normal Clearance
overall width:	14 mm
manufacturer upc number:	029176014215



## China abec 7 Bearing Supplier

bore type:	Round
SRI	4.01
hidYobi	6204
LangID	1
D_	47
SREX	0.04
B_	14
da min	25
hidTable	ecat_NSRDGB
Oil rpm	18000
SRE	4.21
mass	0.107
GRS rpm	15000
ra	1
SRIX	0.02
D_a	42
SRIN	0
C0	6.6
fo	13.1
SREN	0
DE_	41.438
Prod_Type3	DGBB_SR_OT
DA_	7.938
bomp	0
Z_	8
yobi	6204
C_conv	12800
ALPHA_	0
SDM_	33.5
r	1
KBRG	6101
SBRG	2



## China abec 7 Bearing Supplier

DI_	25.562
-----	--------